

Certificate of Conformity/Approval

Certificate No.: SAA-211581-EA

Certificate Holder: Shell Electronic Limited

2FI., BC Building, 3# of Shayuan 1st Road, Keyuancheng, Tangxia Town, 523710 Dongguan,

Guangdong P.R. China

Regulatory Definition: Power Supply or Charger

Product Description: AC Adapter (Direct Plug-in Type)

Trade Name/s: Shell Electronic Limited

Model No.: S-TR-155DAA

Rating/Marking/s: Input: 100-240V~ 50/60Hz 1.5A

Output Type-C (PD): 5.0Vdc 3.0A 15.0W; 9.0Vdc 3.0A 27.0W;

12.0Vdc 3.0A 36.0W; 15.0Vdc 3.0A 45.0W;

20.0Vdc 3.25A 65.0W;

3.3-16.0Vdc 2.5A 8.25-40.0W;

Total: 65.0W Max

Class II

Standard/s: AS/NZS 62368.1:2018

Condition/s: For use with iPhone mobile phones

Approval Marks: RCM (In accordance with AS/NZS 4417 and EESS requirements)

and

SAA-211581-EA (In accordance with NSW legislative requirements)

Initial Issue Date: 2 August 2021 Expiry Date: 2 August 2026

For and on Behalf of SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein. For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au

JAS-ANZ

www.jas-anz.org/register



Issued: 03-08-21 211581 Corrected Page 1 of 3



Certificate of Conformity/Approval

Trade Name	Rating/Marking
LT-TR-155DAA Shell Electronic Limited	Input: 100-240V~ 50/60Hz 1.5A Output Type-C (PD): 5.0Vdc 3.0A 15.0W; 9.0Vdc 3.0A 27.0W; 12.0Vdc 3.0A 36.0W; 15.0Vdc 3.0A 45.0W 20.0Vdc 3.25A 65.0W; 3.3-16.0Vdc 2.5A 8.25-40.0W;
	Total: 65.0W Max Class II
S-TR-155DBA Shell Electronic Limited	Input: 100-240V~ 50/60Hz 1.5A Output Type-C (PD): 5.0Vdc 3.0A 15.0W; 9.0Vdc 3.0A 27.0W; 12.0Vdc 3.0A 36.0W; 15.0Vdc 3.0A 45.0W 20.0Vdc 2.25A 45.0W; 20.0Vdc 3.25A 65.0 3.3-16.0Vdc 2.5A 8.25-40.0W;
	Total: 65.0W Max Class II
LT-TR-155DBA Shell Electronic Limited	Input: 100-240V~ 50/60Hz 1.5A Output Type-C (PD): 5.0Vdc 3.0A 15.0W; 9.0Vdc 3.0A 27.0W; 12.0Vdc 3.0A 36.0W; 15.0Vdc 3.0A 45.0W 20.0Vdc 2.25A 45.0W; 20.0Vdc 3.25A 65.0
	3.3-16.0Vdc 2.5A 8.25-40.0W; Total: 65.0W Max
	Class II
S-TR-155DCA Shell Electronic Limited	Input: 100-240V~ 50/60Hz 1.5A Output Type-C (PD): 5.0Vdc 3.0A 15.0W; 9.0Vdc 3.0A 27.0W; 12.0Vdc 3.0A 36.0W; 15.0Vdc 3.0A 45.0W 20.0Vdc 2.25A 45.0W; 3.3-16.0Vdc 2.0A 6.6-32.0W;
	Total: 45.0W Max Class II
LT-TR-155DCA Shell Electronic Limited	Input: 100-240V~ 50/60Hz 1.5A Output Type-C (PD): 5.0Vdc 3.0A 15.0W; 9.0Vdc 3.0A 27.0W; 12.0Vdc 3.0A 36.0W; 15.0Vdc 3.0A 45.0W 20.0Vdc 2.25A 45.0W; 3.3-16.0Vdc 2.0A 6.6-32.0W;
	Total: 45.0W Max
	Shell Electronic Limited Shell Electronic Limited Shell Electronic Limited

For and on Behalf of SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein. For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au

JAS-ANZ

Class II

www.jas-anz.org/register



Issued: 03-08-21 211581 Corrected Page 2 of 3



Certificate of Conformity/Approval

Additional Models

S-TR-155DDA

Trade Name

Shell Electronic Limited

Rating/Marking

Input: 100-240V~ 50/60Hz 1.5A

Output Type-C (PD): 5.0Vdc 3.0A 15.0W; 9.0Vdc 3.0A 27.0W;

12.0Vdc 2.5A 30.0W; 15.0Vdc 2.0A 30.0W;

20.0Vdc 1.5A 30.0W:

3.3-16.0Vdc 2.0A 6.6-32.0W:

USB (QC): 5.0Vdc 3.0A 15.0W: 9.0Vdc 2.0A 18.0W:

Total: 45.0W Max

Class II

Output Type-C (PD): 5.0Vdc 3.0A 15.0W; 9.0Vdc 3.0A 27.0W;

12.0Vdc 3.0A 36.0W; 15.0Vdc 3.0A 45.0W;

20.0Vdc 2.25A 45.0W;

3.3-16.0Vdc 2.0A 6.6-32.0W:

USB (QC): 5.0Vdc 3.0A 15.0W; 9.0Vdc 2.0A 18.0W;

Total: 45.0W Max

Class II

LT-TR-155DDA Shell Electronic Limited Input: 100-240V~ 50/60Hz 1.5A

Output Type-C (PD): 5.0Vdc 3.0A 15.0W; 9.0Vdc 3.0A 27.0W;

12.0Vdc 2.5A 30.0W; 15.0Vdc 2.0A 30.0W;

20.0Vdc 1.5A 30.0W:

3.3-16.0Vdc 2.0A 6.6-32.0W;

USB (QC): 5.0Vdc 3.0A 15.0W; 9.0Vdc 2.0A 18.0W;

Total: 45.0W Max

Class II

Output Type-C (PD): 5.0Vdc 3.0A 15.0W; 9.0Vdc 3.0A 27.0W;

12.0Vdc 3.0A 36.0W; 15.0Vdc 3.0A 45.0W;

20.0Vdc 2.25A 45.0W;

3.3-16.0Vdc 2.0A 6.6-32.0W:

USB (QC): 5.0Vdc 3.0A 15.0W; 9.0Vdc 2.0A 18.0W;

Total: 45.0W Max

Class II

For and on Behalf of SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein. For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au

www.jas-anz.org/register



Issued: 03-08-21 211581 Corrected Page 3 of 3